



US 20050008120A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2005/0008120 A1**
(43) **Pub. Date:** **Jan. 13, 2005**(54) **X-RAY INSPECTION SYSTEM****Publication Classification**(75) Inventor: **Michael P. Ellenbogen**, Wayland, MA
(US)(51) **Int. Cl.⁷** **G01N 23/04**(52) **U.S. Cl.** **378/57**

Correspondence Address:

Randy J. Pritzker
Wolf, Greenfield & Sacks, P.C.
600 Atlantic Avenue
Boston, MA 02210-2206 (US)(57) **ABSTRACT**(73) Assignee: **L-3 Communications Security and**
Detection Systems Corporation Dela-
ware, Woburn, MA (US)(21) Appl. No.: **10/912,874**(22) Filed: **Aug. 6, 2004****Related U.S. Application Data**(63) Continuation of application No. 10/732,581, filed on
Dec. 10, 2003, which is a continuation of application
No. 10/115,443, filed on Apr. 3, 2002, now aban-
doned.(60) Provisional application No. 60/281,117, filed on Apr.
3, 2001.

An X-ray inspection system and methodology is disclosed. The system comprises a conveyor, an X-ray source that exposes an item under inspection to X-ray radiation and at least one X-ray detector that detects X-ray radiation modified by the item. The X-ray source and X-ray detector may be movable in any of first and second dimensions. The X-ray source may also be moved in a third dimension to zoom in and out on regions of interest in the item under inspection. The system further comprises a controller that controls movement of the X-ray source and X-ray detector, independently of each other, in any of collinear and different directions, to provide a plurality of X-ray views of the item at varying examination angles of the X-ray radiation. A processor coupled to the controller may be configured to receive and process detection information from the X-ray detector and to provide processed information to an operator interface. The operator interface may also receive instructions from an operator input and provide the instructions to the controller.

